

Product Specification Sheet

Rev. 03-AUG-2023

100P™ Fine Line

SPECIFICATIONS

Item #:

 10201FL Black
 10202FL Blue
 10203FL Green
 10204FL Red

 10205FL White
 10206FL Yellow
 10207FL Orange
 10209FL Bright Green

 10211FL Pink
 10212FL Violet
 10213FL Light Blue
 10215FL Brown

10210FL Silver 10214FL Gold 10200FL Replacement Tip



Scan for website

Style: Valve ActivatedTip Type: Fine Line

• Barrel Material: Aluminum

• Fill quantity: 10 ml

• Marking Width: 1.5 mm (0.059")

• Dimensions*: 5.69" L x 0.56" Ø (144 mm x 14 mm) *taken w/ marker capped

• Marking Temp. Range: -50° to 150° Fahrenheit (-45° C to 65° C)

• Dry Time: approx. 45 sec.

• Quantity/ Weight Per Box*: 12 ea./ 0.75 lb. (340 g) *other packaging options available

• Quantity/ Weight Per Case: 144 ea./ 9 lb. (4.1 kg)

• Directions For Use: Shake vigorously with cap on. Press tip until inked. Replace cap after use

PRODUCT FEATURES

- High Performance industrial paint is dispensed through a precision valve to ensure smooth paint flow.
- Heavy duty aluminum barrel and air-tight cap withstand industrial use.
- Oil-based paint has exceptional outdoor durability and UV resistance and adheres to rusty and oily metals.
- Marker fits in U-Holder™.
- Made in USA.

TYPICAL USES

- Marks well on rusty and oily metals, dry or damp wood, glass, plastics, rubber tape, cardboard, waxed cartons, ceramics, tiles, concrete, and more.
- Automotive and steel recyclers, surveyors, auto repair shops.

SAFETY INFORMATION

- Read SDS before using (available online at <u>www.umarkers.com</u>).
- Keep out of reach of children. For professional use only.