

Product Specification Sheet

Rev. 01-AUG-2023

A30[™] Paint Marker

SPECIFICATIONS

Item #:

10301 Black 10305 White 10302 Blue 10306 Yellow 10303 Green 10307 Orange 10304 Red 14000 Replacement Tip

Scan for website

- Style: Valve Activated
- Tip Type: Broad Chisel Tip
- Barrel Material: Aluminum
- Fill quantity: 17 ml
- Marking Width: 7 mm (0.118") 5 mm (0.196") 3 mm (0.118")
- Dimensions*: 5.45" L x 0.75" \emptyset (144 mm x 19 mm) *taken w/ marker capped
- Marking Temp. Range: -50° to 150° Fahrenheit (-45° C to 65°C)
- Dry Time: approx. 20 sec.
- Quantity/ Weight Per Box**: 6 ea./ 0.7 lb. (310 g) **other packaging options available
- Quantity/ Weight Per Case: 72 ea./ 8 lb. (3.7 kg)
- Directions For Use: Shake vigorously with cap on. Press tip until inked. Replace cap after use

PRODUCT FEATURES

- Broader marks provide better visibility and are easier to read. Ideal for use on signs, large objects, and packaging materials.
- Quick-draw belt holster has a built-in cap and allows use of the marker with one hand, eliminating the need to re-cap.
- Heavy Duty, 3/4" diameter aluminum barrel and Megaflow[™] patented valve (US Patent No: 7,182,541 B1) ensures smooth paint flow. Durable tip resists abrasion.
- Permanent xylene free paint.
- Made in USA.

TYPICAL USES

- Wherever broad, bold markers are necessary.
- Industrial marking for quality assurance, color coding and parts identification.
- Marking of tools, inventory, and work-in-progress.
- Welding, steel fabrication, construction.

SAFETY INFORMATION

- Read SDS before using (available online at <u>www.umarkers.com</u>).
- Conforms to ASTM D4236.
- Keep out of reach of children. For professional use only.

